

## Triple Eccentric Wafer Butterfly Valve

### Product Description

Name	Description
Model	D373H-16/25C
Name	Triple Eccentric Butterfly Valve
Size	DN40-2000
Pressure	PN16/25
Temp.	-29~425°C
Suitable Medium	Water, weak acid base, air, steam, oil, etc.
Body	WCB/CF3/CF3M/CF8/CF8M
Seat	430+Graphite/13Cr/304/316
Disc	WCB/CF3/CF3M/CF8/CF8M
Shaft	2Cr13/304/316
Actuator	Worm Gear/Electric/Pneumatic

### Executive Standard

Name	Standard
Design and Manufacture	GB/T 12238
Face to face Length	GB/T 12221
End Flange	EN 1092-1
Pressure Test	GB/T 13927

### Dimensions

Size			PN16		PN25	
DN	NPS(Inch)	L	D1	N-d	D1	N-d
40	3/4"	43	110	4-18	110	4-18
50	2"	43	125	4-18	125	4-18
65	2 1/2"	46	145	4-18	145	8-18
80	3"	49	160	8-18	160	8-18
100	4"	56	180	8-18	190	8-22
125	5"	64	210	8-18	220	8-26
150	6"	70	240	8-22	250	8-26
200	8"	71	295	12-22	310	12-26
250	10"	76	355	12-26	370	12-30
300	12"	83	410	12-26	430	16-30
350	14"	92	470	16-26	490	16-33
400	16"	102	525	16-30	550	16-36
450	18"	114	585	20-30	600	20-36
500	20"	127	650	20-33	660	20-36
600	24"	154	770	20-36	770	20-39
700	28"	165	840	24-36	875	24-42
800	32"	190	950	24-39	990	24-48
900	36"	203	1050	28-39	1090	28-48
1000	40"	216	1170	28-42	1210	28-56
1200	48"	254	1390	32-48	1420	32-56
1400	56"	279	1590	36-48	1640	36-62
1600	64"	318	1820	40-56	1860	40-62
1800	72"	356	2020	44-56	2070	44-70
2000	80"	406	2230	48-62	2300	48-70

